History of original corner establishment:

Original survey by Herman D. Gradin under GLO contract number 452, dated June 16, 1882. Official record states:

Marked 13" \times 8" \times 6" basalt stone - corner to Sec. 19, 20, 29, 30, T4S, R37E:

 $12^{\prime\prime}$ pine bears N $30\,^{\circ}$ W 193 lks. dist. $30^{\prime\prime}$ pine bears S $25\,^{\circ}$ E 130 lks. dist.

24" fir bears N 30° E 110 1ks. dist.

DIAGRAM	
T4S,	R37E
19	20
30	29

Description of corner evidence found:

Found mound stone with stone $13'' \times 8'' \times 6''$ marked with 5 chisel marks one side, 2 on other side.

Found 18" diameter pine snag, bears N 29° W 128.3 ft. to stone (scribe "T4S, R37E, S19 BT"). Found 35" diameter dead & downed tree, bears S 70° W a distance of 74.8 ft. from stump to stone (scribed "T4S, R37E, S30 BT").

Found 36" diameter Douglas Fir, bears N 36° E a distance of 74.9 ft. (scribed "T4S, R37E, S20 BT").

Description of monument and accessories I established to perpetuate the original location of this corner:

At the cental point of the marked stone, we set a $2" \times 30"$ galvinized iron pipe, 15" in the ground & mounded to 4" from top with stones & dirt.

From which:

Orig. BTS as described above.

LS 1952 T4S R37E 19 20 29

New BTS as follows:

18" Pondora Pine scribed "T4S, R37E, S20 BT" on dble blaze, bears N 55° E a distance of 112.5 ft.

8" Red Fir scribed "T4S, R37E, S29, BT" on dble blaze, bears S 45° E a distance of

12" Red Fir scribed "T4S, R37E, S30 BT" bears S 76° W a distance of 87.4 ft.

Magnetic compass (20° East declination) steel tape

REGISTERED PROFESSIONAL LAND SURVEYOR

Witnesses: Norman Paullus, Jr. Gary Keenan

ONEGON NORMAN J. PAULLUS JR.

Office of County of	
State of , I hereby certify that the within instrument was filed in this o	Hica
for record on the day of, 19	HOINU

..... by (COUNTY OFFICIAL) (DEPUTY)

COUMTY SURVEYOR

Date Received 9-26-83

Date Filed 9-28-83

Form R6-7100-57 (9/71)