CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1882 by Herman D.Gradin under General Land Office Contract No. 452. Surveyor General Record states:

Set post for corner from which:

A fir 12 in. dia. bears \$10W, 14 links

The old 4 section corner bears South, 50 links

x-25		
DIAGRAM		
T4S		
R37E	R38E	
५ s 36		

No record of subsequent remonumentation found in County records. Description of corner evidence found:

ORIGINAL BT

A white fir 23 in. dia. bears \$34W, 10.0 feet, live, scribes visable

See map of survey dated June 1980 Description of monument and accessories I established to perpetuate the original location of this corner:


At record distance from BT and on the range line, I set a $2^{\frac{1}{2}}$ ' x 30" iron pipe with brass cap marked as shown, 27" in ground, from which:

NEW BTs:

A 13 in. dia. fir bears \$73W, 32.3 feet marked 4 \$36 BT

A 6 in. dia. White fir bears N37W, 18.1 feet marked X BT

The West & corner of section 31 bears South 33.3 feet



File No. 519-84 R

PROFESSIONAL LAND SURVEYOR

Brass washer nailed to B.T.blaze. Used steel tape and magnetic compass with 18° East declination. Measured to center of all B.T.s

Office of			
State of, I hereby certify the	, 19 UN	ION COUNTY	
(COUNTY OFFICIAL)	(DEPUTY)	SURVEYOR	
Form R6-7100-57 (9/71)	Or to Re	ceived	
	Date Fil	ed	
	Ву	,	