


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

A-1

History of original corner establishment:

The original survey was performed by T. Davenport as part of the GLO Survey in 1863. This survey of the South boundary of T. 3 S., R. 38 E. was under contract #102. The GLO record states:

- At the corner point a post was set from which:
- A tamarack, 9 ins. diam. bears S. 35° E., 12 lks. dist.
- A spruce, 8 ins. diam. bears S 55° W., 15 lks. dist.
- A spruce, 10 ins. diam. bears N. 20° W., 6 lks. dist.
- A tamarack, 6 ins. diam. bears N. 60° E. 46 lks. dist.



In 1882, H. Graden performed a re-survey under contract #452. At the corner point two new bearing trees were made to replace the missing spruce bearing trees:

- A tamarack, 12 ins. diam. bears S. 72° W., 56 lks. dist.
- A tamarack, 10 ins. diam. bears N. 5° W., 33 lks. dist.

Description of corner evidence found:

- A 14 ins. diam. 24 in. high sawed and partially rotted stump bears N. 60° E., 30.4 ft. dist. mkd. with only a visible "T".
- A 14 in. diam. 18 in. high sawed and rotted stump bears N. 5° W., 21.8 ft. dist.
- A 20 in. diam. live tamarack bears S. 72° W., 37.0 ft. dist., marked with a chopped into blaze, but no scribing visible. Scribe is probably further into the tree.

Description of monument and accessories established to perpetuate the original location of this corner:

Set a 1-inch x 30-in. iron pipe with a 2½ in. brass cap, 24 ins. in the ground, surrounded by a 36 in. diam. stone mound. The cap is marked as shown in the above diagram. The corner was reestablished from the found bearing trees.

New bearing trees:

- A white fir, 11 ins. diam. bears N. 1° W., 14.8 ft. dist., mkd. T3S R37E S36 BT.
- A lodgepole pine, 7 ins. diam., bears N. 64° E., 19.4 ft. dist., mkd. T3S R38E S31 BT.
- A white fir, 10 ins. diam., bears S. 28° E., 6.9 ft. dist., mkd. T4S R38E S6 BT.

Set a steel fence post alongside the monument, painted the blazes on the bearing trees red.

I certify the above monument and references were properly reestablished under my supervision on May 29, 1986, and witnessed by Tom Fisk and Larry McBroom.

UNION COUNTY SURVEYOR

Date Received 5-1-89

Date Filed 5-15-89

By G. LANGLITZ, DEPUTY

File No. 110-89 R

REGISTERED PROFESSIONAL LAND SURVEYOR

James D. Hanley

OREGON
 SEPTEMBER 23, 1977
 JAMES D. HANLEY
 1206

Office of..... County of.....

State of....., I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19.....

..... by
 (COUNTY OFFICIAL) (DEPUTY)