

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

C-5


**History of original corner establishment:**

The original survey of Township 4 South, Range 38 East was performed by W. B. Barr under GLO Contract No. 388, dated May 7, 1881.

**Record states:**

Marked volcanic rock 16 x 14 x 12 ins. for 1/4 sec. cor. from which:

- Fir 24 ins. diam. bears S. 25° E., 25 lks. dist.
- Fir 12 ins. diam. bears S. 84° W., 12 lks. dist.



**Description of corner evidence found:**

Found vesicular basalt stone 16 x 14 x 10 ins. marked with 1/4 on downward face, lying in a 6 stone mound, from which:

A stump hole bears S. 25° E., 16.5 feet dist., no trace of bearing tree other than bark remains.

A Douglas Fir 22 ins. diam. stump, sawed 4.5 feet height bears S. 84° W., 7.9 feet dist., marked with 1/4 scribe visible on open face and faint lower trunk scar.

**Description of monument and accessories established to perpetuate the original location of this corner:**

At the point of the recovered corner stone, set a 2½-in. brass cap on a 1¼-in. diam. galv. iron pipe, 30 ins. long, 26 ins. into the ground and constructed a 36-in. diam. stone mound around it. Buried the original stone 1 ft. North of the monument. Cap is marked as shown in the above corner diagram.

**From the corner point:**

A 12 in. diam. white fir bears N. 73° W., 40.9 ft. dist., mkd. ¼ S6 BT on a double blaze.

A secure basalt stone 18 ins. x 18 ins. protruding 6 ins. above ground bears N. 71° E., 11.8 ft. dist., mkd. X B0 on the Southerly sloping face.

A secure basalt stone 36 ins. x 30 ins. protruding 6 ins. above ground bears S. 32° W., 18 ft. dist. mkd. X B0 on top.

A secure basalt stone 24 ins. x 12 ins. protruding 6 ins. above ground bears S. 77° E., 17.6 ft. dist., mkd. X B0 on top.

Set a steel fence post 3 ft. East of the corner with USFS 54-9 sign attached. Also attached 54-3 tag to original bearing tree and both 54-9 sign and 54-3 tag to the new bearing tree.

I certify the above monument and references were properly reestablished under my supervision April 30, 1992, witnessed by Tom Fisk and Larry McBroom.

Office of..... County of.....  
State of....., I hereby certify that the within instrument was filed in this office  
for record on the..... day of....., 19.....

..... by.....  
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*James D. Hanley*  
OREGON  
SEPTEMBER 23, 1977  
JAMES D. HANLEY  
1206

**UNION COUNTY  
SURVEYOR**

Date Received 7/8/92

Date Filed 7/17/92

By Gregory T. Blake

File No. 045-1992 R.

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

C-5


History of original corner establishment:

The original survey of Township 4 South, Range 38 East was performed by W. B. Barr under GLO Contract No. 388, dated May 7, 1881.

Record states:

Marked volcanic rock 16 x 14 x 12 ins. for 1/4 sec. cor. from which:

- Fir 24 ins. diam. bears S. 25° E., 25 lks. dist.
- Fir 12 ins. diam. bears S. 84° W., 12 lks. dist.



Description of corner evidence found:

Found vesicular basalt stone 16 x 14 x 10 ins. marked with 1/4 on downward face, lying in a 6 stone mound, from which:

A stump hole bears S. 25° E., 16.5 feet dist., no trace of bearing tree other than bark remains.

A Douglas Fir 22 ins. diam. stump, sawed 4.5 feet height bears S. 84° W., 7.9 feet dist., marked with 1/4 scribe visible on open face and faint lower trunk scar.

Description of monument and accessories established to perpetuate the original location of this corner:

At the point of the recovered corner stone, set a 2½-in. brass cap on a 1¼-in. diam. galv. iron pipe, 30 ins. long, 26 ins. into the ground and constructed a 36-in. diam. stone mound around it. Buried the original stone 1 ft. North of the monument. Cap is marked as shown in the above corner diagram.

From the corner point:

A 12 in. diam. white fir bears N. 73° W., 40.9 ft. dist., mkd. ¼ S6 BT on a double blaze.

A secure basalt stone 18 ins. x 18 ins. protruding 6 ins. above ground bears N. 71° E., 11.8 ft. dist., mkd. X B0 on the Southerly sloping face.

A secure basalt stone 36 ins. x 30 ins. protruding 6 ins. above ground bears S. 32° W., 18 ft. dist. mkd. X B0 on top.

A secure basalt stone 24 ins. x 12 ins. protruding 6 ins. above ground bears S. 77° E., 17.6 ft. dist., mkd. X B0 on top.

Set a steel fence post 3 ft. East of the corner with USFS 54-9 sign attached. Also attached 54-3 tag to original bearing tree and both 54-9 sign and 54-3 tag to the new bearing tree.

I certify the above monument and references were properly reestablished under my supervision April 30, 1992, witnessed by Tom Fisk and Larry McBroom.

Office of..... County of.....  
State of..... I hereby certify that the within instrument was filed in this office  
for record on the..... day of....., 19.....

..... by .....  
(COUNTY OFFICIAL) (DEPUTY)

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*James D. Hanley*

OREGON  
SEPTEMBER 23, 1977  
JAMES D. HANLEY  
1206

CLATSOP COUNTY

FILED

7/18/92

7/17/92

By *Bryon T. Black*

File No. 045-1992C