


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

The original survey of Township 4 South, Range 38 East was performed by A. B. Barr under contract No. 588, dated May 7, 1881. GLO record states:



Marked basalt rock 18" x 14" x 10" from which:

A pine 56" dia. bears S 27 L 19 lks. dist.

A pine 20" dia. bears N 2 W 70 lks. dist.

Description of corner evidence found:

Found well set stone 18" x 14" x 10" with faint ¼ on south face. From which:

A 24" dia. burned and rotted Ponderosa Pine stump bears N 2 W 46.2 ft. dist. marked with chop marks.

A 36" dia. burned and rotted Ponderosa Pine bears S 42 E 9.3 ft. dist. marked with chop marks and partial scribing.

Description of monument and accessories established to perpetuate the original location of this corner:

At the point of the recovered stone, set 2½" brass cap on 1¼" dia. galv. iron pipe, 30" long, 24" into the ground with 36" dia. stone mound. Deposited the original stone 1' north of the monument in the stone mound. From the corner point:

A 10" White Fir bears N 60 W 29.6 ft. dist. marked ¼ S6 BT

A 16" Tamarack bears S 40 E 45.5 ft. dist. marked ¼ S7 BT

Set a steel fence post alongside the monument, painted the blazes on the bearing trees red, and attached a brass I. D. washer between the B and T scribes.

I certify the above monument and references were properly reestablished under my supervision in August 1988.


Witnessed by Tom Fisk, Larry McBroom and Andy Marlette.

E-3

Office of..... County of.....
State of....., I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19.....

..... by
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)



James D. Hanley
OREGON
REGISTERED
JAMES D. HANLEY
1988

UNION COUNTY SURVEYOR
Date Received <u>5-1-89</u>
Date Filed <u>5-15-89</u>
By <u>G. LANGLITZ DEPUTY</u>
File No. <u>106-89 R</u>