


**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**

**HISTORY OF ORIGINAL CORNER ESTABLISHED:**

Corner originally established by W.B. Barr under GLO contract 388, dated May 7, 1881. Surveyor General field notes state:

Set Stake 4 ft. long 4 in. diam. 18 in. ground for 1/4 sec corner, from which:  
Black Pine 6 in. diam. bears N77°E, 4 lks. dist.  
Black Pine 6 in. diam. bears S83°W, 32 lks. dist.

T 4 S R38S E T-05



**DESCRIPTION OF CORNER EVIDENCE FOUND:**  
None.

SEE SURVEY NUMBER 018-2016

**DESCRIPTION OF MONUMENT AND ACCESSORIES I ESTABLISHED**

**TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:**

At a proportionate position, I set a 2 1/2" x 30" aluminum pipe with 2 1/2" aluminum cap, marked as shown below, 14 inches in the ground, in a collar of stone 2' diam, from which:

**NEW BEARING OBJECTS:**

- A 7" Lodgepole Pine bears North 34° East, a distance of 26.45 feet, marked 1/4 S29 BT.
- A 6" Lodgepole Pine bears South 71° East, a distance of 9.10 feet, marked 1/4 S29 BT.
- A 6" Lodgepole Pine bears South 40° West, a distance of 0.90 feet, marked 1/4 S30 BT.
- A 6" Lodgepole Pine bears North 2° West, a distance of 20.75 feet, marked 1/4 S30 BT.

Set a steel fencepost approximately 1 foot North of the corner monument.  
I hereby certify that this monument was set June 21, 2016.

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR



OREGON  
June 2, 2010  
JEFFREY S. HSU  
83571

Renewal Date: June 30, 2017

BAGETT - GRIFFITH & BLACKMAN

T4S R38E

1/4

S30 | S29

2016  
OPLS 83571

**UNION COUNTY  
SURVEYOR**

Date Received 6/27/16

Date Filed 6/27/16

Filed By [Signature]

File Number 021-2016R

I use a steel tape and magnetic compass in the establishment of the bearing trees. Magnetic declination used was 15° East. Distances to the new trees are to a spike in the root crown of the trees. Bearings are to a brass washer in the lower blaze marked OPLS 83571.