V-1

T4S

R38E

\$ 30

S 31

DIAGRAM

R37E

S 36

History of original corner establishment: Corner established in 1863 by Timothy W.Davenport under General Land Office Contract No. 102. Surveyor General Record states:

Set post for corner from which;

A spruce 12 in. dia. bears N2OW, 13 links

A tamarack 5 in. dia. bears \$35W, 15 links

A spruce 6 in. dia. bears S65E, 16 links

A spruce 10 in. dia. bears N87E, 27 links Retracement calls for removing of scribes on BTs west of range line

Retraced in 1881 by W.B.Barr under General Land Office Contract No.388. No record of subsequent remonumentation was found in County records. Description of corner evidence found:

Found a tamarack 12 in. dia. I opened and found blaze with scribes removed at a dia. of 5^\pm in. I accept this as the SW BT as originally taken by Davenport.

I found very badly rotted out remains of trees at the record bearing and distance in the NE and SE quadrants.

See map of survey dated June 1980.

Description of monument and accessories I established to perpetuate the original location of this corner:

At record bearing and distance from the SW BT, I set a $2\frac{1}{2}$ inch x 30 inch iron pipe with brass cap marked as shown, 24 inches in the ground from which;

NEW BTs


A 9 in. dia. fir bears N1E, 28.3 feet marked T4S R38E S30 BT

A 10 in. dia. fir bears \$23E, 24.6 feet, marked T4S R38E \$31 BT

ORIGINAL BT

A 12 in. dia. tamarack bears \$35W, 9.9 feet blaze only

The NE corner of Section 36, T4S R37E, bears North 66.8 feet





Brass washer nailed to 8.T.blaze. Used steel tape and magnetic compass with 18 East declination. Measured to center of all B.T.s

State of	······ , 13	SURVEYOR
COUNTY OFFICIALI	(DEPUTY)	••••••

Form R8-7100-57 (9/71)

F27 040