UNION COUNTY SURVEYOR

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

HISTORY OF ORIGINAL CORNER ESTABLISHMENT:

Corner originally established by W.B. Barr under GLO Contract Number 388, dated May 7, 1881. Surveyor General record states:

Marked basalt rock 16x15x5 inches for 1/4 Sec Cor. Raised mound of rock as per instructions

No record of subsequent monumentation found in Union County survey records.

T4S R38E V-19 S|26

DESCRIPTION OF CORNER EVIDENCE FOUND:

Found no evidence of the original corner monument or mound

See Survey No. 015-2003

DESCRIPTION OF MONUMENT AND ACCESSORIES I ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

At the position determined by said survey, I set a 2 $\frac{1}{2}$ " x 30" aluminum pipe with aluminum cap marked as shown below, 28" in the ground, from which:

New Bearing Objects:


A 5/8" x 30" iron pin with 1 $\frac{1}{2}$ " aluminum cap bears N 37°13'E, a distance of 33.35 feet, marked BGB SURVEY MARKER NE RP. A 5/8" x 30" iron pin with 1 $\frac{1}{2}$ " aluminum cap bears S 46°41'E, a distance of 23.56 feet, marked BGB SURVEY MARKER SE RP. (Falls in E-W fence line)

A $5/8" \times 30"$ iron pin with 1 ½" aluminum cap bears S 47°18'W, a distance of 22.52 feet, marked BGB SURVEY MARKER SW RP. (Falls in E-W fence line) A 5/8" x 30" iron pin with 1 $\frac{1}{2}$ " aluminum cap bears N 21°20'W, a distance of 49.91 feet, marked BGB SURVEY MARKER NW RP.

Set a steel fence post approximately 1 ft. West of monument.

I hereby certify that the corner was monumented on May 13, 2003.

UNION COUNTY SURVEYOR
Date Received 5/23/03
Date Filed 6/14-/03
Filed By Negry T. Oliv
File Number O23 - 2003 R



REGISTERED PROFESSIONAL LAND SURVEYOR

> OREGON July 17, 1986

RICK G. ROBINSON

2219

I used a Leica 530 GPS unit in the establishment of the new accessories. The Basis of Bearing is the same as map of survey number 015-2003. The distances are to the center of a 5/8"x30" iron pin with 1 ½" aluminum cap.

Renewal Date December 31, 2004

V - 19