
CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Adams & Clark, Inc. 1720 W. Fourth Ave. Spokane, WA 99204-1702

Corner Code <u>C-9</u>
Township 4 South, Range 39 East


History of original corner establishment:

"40.00 chains. Set post for 1/4 section corner from which a pine 24 inch diameter bears East 10 links distance a pine 20 inch diameter bears N22°W 39 links distance"



Description of corner evidence found:

Nothing found.



<u>Description of monument and accessories I established to perpetuate the original location of this corner.</u>

Set 5/8"x36" rebar with 1-1/2" aluminum cap marked as shown below.

Accessories set:

5/8"x24" rebar with yellow plastic cap marked "RP LS 1503"


N42°11'14"E 59.08'


S46°02'44"E 60.69'


S20°18'29"W 48.81'

N46°09'08"W 56.98'

Accessory ties were made with electronic total station theodolite, and steel tape.







HORIZONTAL CONTROL DATA

UNION COUNTY, OREGON OREGON STATE PLANE, NORTH ZONE (3601)

STA NAME:

200406

1/4 CORNER COMMON TO SECTIONS 4 and 5

TWP.

4 S. RGE.

39 E.

GEODETIC COORD: NAD 83(91)

DATE TIED: July, 2004

LAT:

45 ° 14 '

44.65445 " N

SURVEYOR:

GREGORY T. BLACKMAN

OPLS 991

LONG:

117° 57'

10.56866 " W

FIRM: BAGETT, GRIFFITH, & BLACKMAN

2006 ADAMS AVENUE

LAGRANDE, OR 97850

(541) 963-6092

SP. COOR: NAD 83(91)

N:

586024.123

INT FT.

E:

8857984.366

INT FT.

TYPE: GPS

THETA:

1 ° 48 ' 22.8324858 "

ORDER: SECOND CLASS: 1

SCALE FACTOR:

0.9998954832


ELEV: 2697.54

US FT.

ELEV: DATUM: NGVD 29

COMMENTS:

Corner is a 5/8" iron pin with 1 1/2" aluminum cap marked as shown: Set by survey number 040-2002



REGISTERED **PROFESSIONAL**

GREGORY T. BLACKMAN

Renewal Date: December 31, 2005

1 METER = 3.2808333333... US FEET = 39.37 INCHES

1 METER = 3.280839895 INT'L FEET OR 1 INCH = 2.54 CM

TO CALCULATE ELEVATION FACTOR (IN THE NORTH AMERICAN CONTINENT)

DIVIDE 20,906,000 BY (20,906,000 + ELLIPSOID ELEV. IN FEET)