UNION COUNTY SURVEYOR

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

HISTORY OF ORIGINAL CORNER ESTABLISHMENT: NONE

No record of subsequent monumentation found in Union County survey records.

DESCRIPTION OF CORNER EVIDENCE FOUND:


NONE

See Survey No. 007-2001

DESCRIPTION OF MONUMENT AND ACCESSORIES I ESTABLISHED

TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

At position established by Survey No. 007-2001 I set a 2 ½" x 30" copper clad monument in a water valve box, marked as shown below, 35" in the ground from which:



A 2" X in a concrete wall on the Southeast corner of a bridge, bears $N18^{\circ}E$, a distance of 80.13 feet.

A 60d spike in a Power Pole 1 ft. above ground, bears $S40^{\circ}E$, a distance of 44.17 feet.

A 60d spike in a Power Pole 1 ft. above ground, bears $S52^{o}W$, a distance of 52.51 feet.

A 2" X in a concrete wall on the Southwest corner bridge, bears $N17^{\,o}W$, a distance of 80.57 feet.

I hereby certify that the corner was monumented on February 14, 2001. Witness: Norbert Volny and Gregory T. Blackman, Jr.

REGISTERED
PROFESSIONAL
AND SURVEYOR

OREGON

GREGORY T. BLACKMAN 991

36

Renewal Date: Dec. 31, 2001

C 1/4 • S 18

COUNTY SURVEY

COUNTY SURVEY

OP 191

UNION COUNTY SURVEYOR

Date Received 3/29/01

Date Filed 3/31/01

Filed By R. ROBINSON, DEPUTY

File Number 013 - 2001 R

I used a compass and steel tape in the establishment of the new accessories. I used 18° East declination. The distances are to the center of a 5/8"x30" rebar with 1 ½" aluminum cap marked Union County Survey Marker or as noted.

HORIZONTAL CONTROL DATA **UNION COUNTY, OREGON OREGON STATE PLANE, NORTH ZONE (3601)**

STA NAME:

200123

CENTER QUARTER OF SECTION 18

TWP.

4 S. RGE.

40 E.

GEODETIC COORD: NAD 83(91)

DATE TIED: 15 FEB. 2001

LAT:

45 ° 13 '

0.95466 " N

SURVEYOR:

GREGORY T. BLACKMAN

LONG:

117° 51'

37.20200 " W

FIRM: BAGETT, GRIFFITH, & BLACKMAN

2006 ADAMS AVENUE

OPLS 991

LAGRANDE, OR 97850

(541) 963-6092

SP. COOR: NAD 83(91)

N:

576293.186

INT FT.

E:

8882164.640

INT FT.

TYPE: GPS

THETA:

1 ° 52 ' 19.2514606 "

ORDER: SECOND CLASS: 1

SCALE FACTOR:

0.9998949354

ELEV: 2794.32

US FT.

ELEV: DATUM: NGVD 29

COMMENTS:

REGISTERED **PROFESSIONAL** ND SURVEYOR GREGORY T. BLACKMAN

991

Renewal Date: Dec. 31, 2001

1 METER = 3.2808333333... US FEET = 39.37 INCHES

1 METER = 3.280839895 INT'L FEET OR 1 INCH = 2.54 CM

TO CALCULATE ELEVATION FACTOR (IN THE NORTH AMERICAN CONTINENT)

DIVIDE 20,906,000 BY (20,906,000 + ELLIPSOID ELEV. IN FEET)