
CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment: Corner originally established by Henry M. Thatcher under GLO contract number 320 dated April 1, 1879. Surveyor General record states:

Set stone 11x11x5 for 4 sec cor from which:

A black pine 10 in dia bears N10°E 11 1ks dist A black pine 11 in dia bears \$30°W 25 1ks dist



Corner was retraced by Alonzo Gesner under GLO contract number 683 dated June 7, Surveyor General record states;

Found stone 3x6x6 inches above ground marked and witnessed as stated by the Surveyor General

No record of subsequent remonumentation found in County records. Description of corner evidence found:

NONE , However, I found a line tree 1.85 feet East dead and down. I found the alignment and distance harmonious with proportionate position.


Description of monument and accessories I established to perpetuate the original location of this corner: At proportionate position I set a 2½'x30" aluminum pipe with aluminum cap marked as shown, 18 inches in the ground and raised a mound of stone with a 3 foot base to top of cap; from which:

A 6 inch Tamarack bears S 32° E, 22.71 feet, marked X BT.

A 6 inch Tamarack bears S 61° W, 25.91 feet, marked 4 S 4 BT.

Set a steel fence post approximately 5 feet West with a 54-9 sign attached.

Corner set 8/13/86 Witness: Greg Blackman, Rick Robinson



Brass washer marked OPLS 644 nailed to BT blaze. Used steel tape and magnetic compass with 200 East declination. Distances to the BTs are to a 50d spike set in right side of tree when facing tree, unless otherwise stated.

AND SURVEYOR OREGON DUANE I. GRIFFITH

REGISTERED

PROFESSIONAL

Office of	County of	
State of	, I hereby certify that the within	instrument was filed in this office
for record on the da	y of, 19	r ·
(COUNTY OF	CIAL, URION CEVUNTY SURVEYOR	(DEPUTY)
Form R6-7100-57 (9/71)	Date Received 10-20-86	☆U.S. GOVERNMENT PRINTING OFFICE - 1983 - 793 - 276
	Date Filed 10-27-86	A-11

亚-12