
## CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner originally established by Henry M. Thatcher under GLO contract number 320 dated April 1, 1879. Surveyor General record states:

Set stone 26x10x6 for cor to secs 3,4,33 and 34 from which: A pine 7 in dia bears N23°E 31 lks dist, A pine 6 in dia bears S60°E 28 lks dist, A pine 6 in dia bears S51°W 19 lks dist, A pine 6 in dia bears N20°W 11 lks dist.



Corner was retraced by Alonzo Gesner under GLO contract number 683, dated June 7, 1898. Surveyor General record states;

Found the corner which is a stone 15x10x6 inches above the ground marked and witnessed as stated by the Surveyor General. The bearing tree in Section 34 has fallen down. After retracing this line, Mr. Gesner called the corner out of acceptable limits for closure and returned to obliterate the BTs to the North and set a closing corner East

No record of subsequent monumentation found in county records Description of corner evidence found:

Found stone 24x11x5 inches firmly set marked with 3 grooves East and West (stone is broken)

Found down tree (6 inch lodgepole pine) with chop marks in vicinity of Southeast BT position. No scribes visible.

Description of monument and accessories I established to perpetuate the

original location of this corner: In place of stone, I set a  $2\frac{1}{2}x30^{\circ}$  aluminum pipe with aluminum cap marked as shown, 28 inches in the ground, from which:

New BTs

A 11 inch diameter Tamarack bears \$55°E 85.38 feet marked T4S R41E \$3 BT A 8 inch diameter Tamarack bears \$12°W 91.44 feet marked T4S R41E \$4 BT

Buried the original stone South and alongside of monument Set steel fencepost approximately 5 feet South with 54-9 sign attached

Corner monumented June 18, 1986 Witnesses: Greg Blackman and Rick Robinson GRIFFITH X T3S R41E S 33 S 4 S 3 S 4 S 3 T4S ON S 1986 644

A-13

OREGON JULY 10, 1984 DUANE I. GRIFFITH

REGISTERED

PROFESSIONAL AND SURVEYOR

Brass washer marked OPLS 644 nailed to BT blaze. Used steel tape and magnetic compass with 20° East declination. Distances to the BTs are to a 50d spike set in right side of tree when facing tree, unless otherwise stated.

State of		hin instrument was 61-1:
************************	FFICIALUNION COUNTY SURVEYOR	(DEPUTY)
	Date Received 7-28-86	☆U.S. GOVERNMENT PRINTING OFFICE - 1983 - 793 - 276
	000 MM 8-13-86	