
CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:
Corner originally established by Henry M. Thatcher under GLO contract number 320 dated April 1, 1879. Surveyor General record states:

Marked a fir 18 in dia for $\frac{1}{4}$ sec cor from which;

A fir 12 in dia bears N70 $^{\rm O}$ E 18 1ks dist A spruce 10 in dia bears S80 $^{\rm O}$ W 20 1ks dist



No record of subsequent remonumentation found in county record. Description of corner evidence found:

NONE

Creek call North is within 10 feet of call. There are several dead and down badly rotted Fir and Spruce in the area, but I am unable to identify any marks. Area has been logged, and also many years ago was burned.

See map of survey number 29-86 filed in the office of the Union County Surveyor Description of monument and accessories lestablished to perpetuate the original location of this corner: At proportioned position, I set a $2\frac{1}{2}$ 1x30" aluminum pipe with aluminum cap marked as shown, 30 inches in the ground and raised a small mound of stone around cap, from which:

A 7 inch Tamarack bears N 34° E, 16.31 feet, marked $\frac{1}{4}$ S5 BT.


An 11 inch Spruce bears N 47° W, 20.86 feet, marked 4 S6 BT.

Set a steel fence post approximately 5 feet South with a 54-9 sign attached.

Corner set: 8/29/86 Witness: Greg Blackman,

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 10, 1984
DUANE I. GRIFFITH
644



Brass washer marked OPLS 644 nailed to BT blaze. Used steel tape and magnetic compass with 20° East declination. Distances to the BTs are to a 50d spike set in right side of tree when facing tree, unless otherwise stated.

Office of	County of	
State of	I hereby certify that the within	Winotrumon A was a file to the same
for record on the da	of UNION COUNTY 19	
(COUNTY OFF	C IAL)	(DEPUTY)
Form R6-7100-57 (9/71)	Date Received 10-20-86	☆U.S. GOVERNMENT PRINTING OFFICE - 1983-793-276
	Date Filed 10-27-86	3-276
卫气	BYG, LANGLIE DEPUTY	C - 5
	File No. 193-86 R	