
## CERTIFIED RECORD OF LAND CORNER MONUMENTATION


History of original corner establishment: Corner originally established by Henry M. Thatcher under GLO contract number 320 dated April 1, 1879. Surveyor General record states:

Set stone 16x12x6 for cor to secs 9,10,15 and 16 Raised stone mound at cor



No record of subsequent monumentation found in county records Description of corner evidence found:

Found stone 14x13x10 inches marked with 4, 3, 2 and 3 grooves in mound of stone



Description of monument and accessories I established to perpetuate the

original location of this corner: In place of stone, I set a 2½ x30" a luminum pipe with a luminum cap marked as shown 28 inches in the ground with mound of stone 2 ft base to top of cap, from which:

New BTs

A 10 inch diameter Red Fir bears N10°E 116.44 feet marked T4S R41E S10 BT

A 18 inch diameter Red Fir bears \$140E 82.89 feet marked T45 R41E \$15 BT


A 13 inch diameter Tamarack bears  $S22^{\circ}W$  94.52 feet marked T4S R41E S16 BT A 26 inch diameter Red Fir bears N10°W 58.74 feet marked T4S R41E S9 BT

Buried the original stone South and alongside of monument Set steel fenceposts approximately 5 feet West with 54-2 sign and approximately 5 feet South with 54-2 and 54-9 signs


Corner monumented July 15, 1986 Witnesses: Greg Blackman and Rick Robinson

> REGISTERED PROFESSIONA! LAND SURVER

**DUANE I. GRIFFITH** 



Brass washer marked OPLS 644 nailed to BT blaze. Used steel tape and magnetic compass with 20° East declination. Distances to the BTs are to a 50d spike set in right side of tree when facing tree, unless otherwise stated.



Form R6-7100-57 (9/71)

\$U.S. GOVERNMENT PRINTING OFFICE - 1983-793-276