

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

V-15

83

*already have
just file
AM*

FIELD NOTES

OF THE

REMONUMENTATION OF CERTAIN ORIGINAL CORNER POINTS,

TOWNSHIP 4 SOUTH, RANGE 41 EAST,

[Lined area for field notes]

Of the WILLAMETTE Meridian,

In the State of OREGON

EXECUTED BY

Stephen D. Albright, Cadastral Surveyor

Under special instructions dated May 3, 19 57, which provided for the surveys
included under Group Number 350, approved May 6, 1957
and assignment instructions dated September 20, 19 71.

Survey commenced October 4, 19 71

Survey completed October 4, 19 71

Remonumentation of Certain Original Corner Points,
T. 4 S., R. 41 E., Willamette Meridian, Oregon

CHAINS

A root hole, bears S. 45° E., 44 lks. dist., with
a down and decayed fir alongside, size indeter-
minate, with scribe marks S34 visible on opened
blaze.

A root hole, bears S. 1° W., 22 lks. dist.

A root hole, bears N. 70° W., 4 lks. dist.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins.
in the ground, with brass cap mkd.

T 4 S R 41 E
S 28 | S 27
S 33 | S 34
1971

OK

from which new bearing trees

A western larch, 14 ins. diam., bears N. 54½° E.,
58 lks. dist., mkd. T4S R41E S27 BT.

A spruce, 16 ins. diam., bears S. 27½° E., 94
lks. dist., mkd. T4S R41E S34 BT.

A spruce, 10 ins. diam., bears S. 25° W., 48 lks.
dist., mkd. T4S R41E S33 BT.

A white fir, 10 ins. diam., bears N. 58° W., 73
lks. dist., mkd. T4S R41E S28 BT.

The ¼ sec. cor. of secs. 27 and 34, monumented with the
original basalt stone, 12 x 8 x 8 ins., loosely set, 2
ins. in the ground, marked ¼ on N. face, from which the
only remaining original bearing tree:

A sawed western larch stump, 28 ins. diam., bears
S. 20° W., 37 lks. dist., with a down larch
alongside, with scribe marks ¼ S BT visible on
open double blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 4 S R 41 E
¼ S 27
S 34
1971

from which new bearing trees

A fir, 8 ins. diam., bears N. 65° W., 53 lks.
dist., mkd. ¼ S27 BT.

A lodgepole pine, 12 ins. diam., bears S. 11½° E.,
110 lks. dist., mkd. ¼ S34 BT.

Deposit corner stone and set 5 ft. steel fence
post alongside iron post.

Need signs on post

DLD
8-2-83
Bth
Live ok
staked 5/4 5/3
Painted

UNION COUNTY
SURVEYOR

Received 9-2-83

Filed 9-12-83

G. LANGLITZ DEPUTY

No. 343-83 R