
CERTIFIED RECORD OF LAND CORNER MONUMENTATION

HISTORY OF ORIGINAL CORNER ESTABLISHED:

Not previously established.

T4S R41 EY-11



DESCRIPTION OF CORNER EVIDENCE FOUND:

None.

DESCRIPTION OF MONUMENT AND ACCESSORIES I ESTABLISHED TO MONUMENT THE LOCATION OF THIS CORNER:

At position by survey I set a 5/8" x 12" iron pin, drilled into rock, with 2 ⅓" aluminum cap marked as shown below, from which:

NEW BEARING OBJECTS:

A large rock outcrop bears North 67° East, a dist. of 27.85 ft., marked X BO on the lower edge.

A 16" Ponderosa Pine bears South 19° East, a dist. of 86.00 ft., marked CS 1/16 S33 BT.

A 5/8" x 12" iron pin bears South, a dist. of 13.00 ft.,

with 1 ½" aluminum cap marked South RP.

Set steel fence post approx. 6.5 ft. South

I hereby certify that the corner was monumented on November 26, 2019.

Witness: Kyle A. Tucker

REGISTERED **PROFESSIONAL** LAND SURVEYOR

OREGON JEFFREY S. HSU 83571

Renewal Date: June 30, 2021

GRIFFITH BAGAT T4S **R41E** C S 1/16 S33 C 2019 **OPLS 83571**

UNION COUNTY **SURVEYOR**

I used a steel tape and magnetic compass with 13° East declination in the establishment of the new accessories. The distance is to a 60d spike driven into the right side of the root crown of the bearing tree. A brass washer marked OPLS 83571 is attached to the BT blaze of the new bearing tree. Bearing and distance is to the center of the X of the rock outcrop.