

416

Dependent Resurvey of the 1st Standard Parallel North
through Range 40 East.

Chains dist., marked A P T 5 N R 40 E S 34 B T (new B. T.)

Thence,

S.89°50'W., continuing measurement.

46.70 Spring branch, 2 lks. wide, course NE.

55.00 Ascend 40 ft. over gradual E. slope.

67.76 Proportionate point for the closing cor. of secs. 3 and 4.

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in
the ground, for closing cor. of secs. 3 and 4, with
brass cap marked

T5NR40E
S34
S 4 | S 3
T4NR40E
C C
1931

from which,

A fir, 17 ins. in diam., bears S.63°E., 32 lks. dist.,
marked T 4 N R 40 E S 3 C C B T

A fir, 11 ins. in diam., bears S.35°W., 33 lks. dist.,
marked T 4 N R 40 E S 4 C C B T

Asc. 50 ft. over gradual NE. slope.

79.00 Top of ascent, bears N. and S., thence over level top.

80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in
the ground, for Stan. cor. of secs. 33 and 34, with
brass cap marked

S C
T5NR40E
S33 | S34
1931

from which,

A pine, 9 ins. in diam., bears N.40°E., 34 lks. dist.,
marked T 5 N R 40 E S 34 S C B T

A pine, 10 ins. in diam., bears N.22°W., 28 lks. dist.,
marked T 5 N R 40 E S 33 S C B T

Land, rolling.

Soil, clay loam, 2nd rate.

Timber, fir, pine, spruce and tamarack.

UNION COUNTY
SURVEYOR

Date Received 3/15/13

Date Filed 3/15/13

By [Signature] DEPUTY

File No. 316-2013R