

Dependent Resurvey of the 1st Standard Parallel North
through Range 40 East.

Chains this tree A P T 5 N R 40 E S 34 B T (old B. T.)

No trace of other old B T.

A fir, 10 ins. in diam., bears N.7°E., 9 lks. dist.,
marked A P T 5 N R 40 E S 34 B T (new B. T.)

A pine, 9 ins. in diam., bears N.10°W., 49 lks. dist.,
marked A P T 5 N R 40 E S 34 B T (new B. T.)

Thence,

S.89°58'W., continuing measurement.

39.50 Spring branch, 2 in. wide, course NE.

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in
the ground, for Stan. $\frac{1}{4}$ sec. cor., with brass cap marked

S C
 $\frac{1}{4}$ S 34

1931

from which,

A fir, 10 ins. in diam., bears N.33°E., 68 lks. dist.,
marked $\frac{1}{4}$ S 34 S C B T

A fir, 9 ins. in diam., bears N.41°W., 116 lks. dist.,
marked $\frac{1}{4}$ S 34 S C B T

40.00 intersect the original Stan. $\frac{1}{4}$ sec. cor. of secs. 34, which

is a point determined from the original bearing trees.

I change this cor. to an angle point.

At true cor. point,

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in
the ground, for angle point, with brass cap marked

A P
T5NR40E
S 34

1931

from which,

A fallen spruce snag, 30 ins. in diam., bears S.22°E.,
16 lks. dist., marked S $\frac{1}{4}$ S B T (old B. T.) I remark
A P T 5 N R 40 E S 34 B T

A fallen spruce snag, 50 ins. in diam., bears N.14°W.,
18 lks. dist., marked S C $\frac{1}{4}$ S B T (old B. T.) destroy
marks.

A fir, 30 ins. in diam., bears N.4°E., 150 lks. dist.,
marked A P T 5 N R 40 E S 34 B T (new B. T.)

A spruce, 18 ins. in diam., bears N.33°W., 135 lks.

T5N 40
Z15

T5N 40
Z15B

UNION COUNTY
SURVEYOR

Date Received 3/15/13

Date Filed 3/15/13

By JJ & L DEPT

File No. 318-2013R