

Dependent Resurvey of the 1st Standard Parallel North
through Range 40 East.

Chains this tree A P T 5 N R 40 E S 34 B T (old B. T.)

No trace of other old B T.

A fir, 10 ins. in diam., bears N.37°E., 9 lks. dist.,
marked A P T 5 N R 40 E S 34 B T (new B. T.)

A pine, 9 ins. in diam., bears N.10°W., 49 lks. dist.,
marked A P T 5 N R 40 E S 34 B T (new B. T.)

Thence,

S.89°58'W., continuing measurement.

59.50 Spring branch, 1 1/2 k. wide, course NE.

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in
the ground, for Stan. 1/4 sec. cor., with brass cap marked

S 34

1931

from which,

A fir, 10 ins. in diam., bears N.33°E., 68 lks. dist.,
marked 1/4 S 34 S C B T

A fir, 9 ins. in diam., bears N.41°W., 116 lks. dist.,
marked 1/4 S 34 S C B T

**UNION COUNTY
SURVEYOR**

Date Received 3/15/13

Date Filed 3/15/13

By [Signature] DEPUTY

File No. 317-201312

3.08 Intersect the original Stan. 1/4 sec. cor. of secs. 34, which
is a point determined from the original bearing trees.
I change this cor. to an angle point.

At true cor. point,

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in
the ground, for angle point, with brass cap marked

A P
T5NR40E
S 34

1931

from which,

A fallen spruce snag, 30 ins. in diam., bears S.22°E.,
16 lks. dist., marked S C 1/4 S B T (old B. T.) I remark
A P T 5 N R 40 E S 34 B T

A fallen spruce snag, 30 ins. in diam., bears N.14°W.,
18 lks. dist., marked S C 1/4 S B T (old B. T.) destroy
marks.

A fir, 30 ins. in diam., bears N.4°E., 150 lks. dist.,
marked A P T 5 N R 40 E S 34 B T (new B. T.)

A spruce, 18 ins. in diam., bears N.33°W., 135 lks.

416

Dependent Resurvey of the 1st Standard Parallel North
through Range 40 East.

Chains dist., marked A P T 5 N R 40 E S 34 B T (new B. T.)

Thence,

S.89°50'W., continuing measurement.

46.70 Spring branch, 2 lks. wide, course NE.

55.00 Ascend 40 ft. over gradual E. slope.

67.76 Proportionate point for the closing cor. of secs. 3 and 4.

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, for closing cor. of secs. 3 and 4, with brass cap marked

T5NR40E
S34
S 4 | S 3
T4NR40E
C C
1931

T4N 40 A 13

from which,

A fir, 13 ins. in diam., bears S.65°E., 32 lks. dist., marked T 4 N R 40 E S 3 C C B T

A fir, 11 ins. in diam., bears S.35°W., 33 lks. dist., marked T 4 N R 40 E S 4 C C B T

Asc. 50 ft. over gradual NE slope.

79.00 Top of ascent, bears N. and S., thence over level top.

80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, for Stan. cor. of secs. 33 and 34, with brass cap marked

S C
T5NR40E
S33 | S34
1931

T5N 40
213

from which,

A pine, 9 ins. in diam., bears N.40°E., 34 lks. dist., marked T 5 N R 40 E S 34 S C B T

A pine, 10 ins. in diam., bears N.22°E., 28 lks. dist., marked T 5 N R 40 E S 33 S C B T

Land, rolling.

Soil, clay loam, 2nd rate.

Timber, fir, pine, spruce and tamarack.

UNION COUNTY
SURVEYOR

Date Received 3/12/13

Date Filed 3/15/13

By [Signature]

File No. 317-2013R