

Dependent Resurvey of the 1st Standard Parallel North
through Range 40 East.

Chains

Thence, . . .
~~S. 8. 152' W., resurveying the S. bdy. of sec. 36
 Asc. 130 ft. over SE. slope, through S. end of clearing.
 5.00 Enter second growth timber and brush, bears N. and S.
 11.30 Spur, slopes S., desc. 300 ft. over SW. slope.
 25.00 Head of ravine, course S., asc. 435 ft. over SE. slope.
 27.10 Spring branch, 1 lk. wide, course S.
 36.00 Top of ascent, bears NE. and SW., thence along S. slope.~~

38.18 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in
 the ground, for Stan. $\frac{1}{4}$ sec. cor., with brass cap marked

S C
 $\frac{1}{4}$ S 36
 1931

from which,

A fir, 16 ins. in diam., bears N. 52° E., 74 lks. dist.,
 marked $\frac{1}{4}$ S 36 S C B T

A pine, 26 ins. in diam., bears N. 78° W., 55 lks. dist.,
 marked $\frac{1}{4}$ S 36 S C B T

39.67 Intersect the original Stan. $\frac{1}{4}$ sec. cor., established
 for sec. 36, which is a point determined from the original
 bearing tree to the northwest.

I change this cor. to an angle point as follows:

At true cor. point

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in
 the ground, for angle point, with brass cap marked

A P
 T5NR40E
 S 36

1931

from which,

A dead fallen pine, 40 ins. in diam., bears N. 44° W., 36
 lks. dist., marked S C $\frac{1}{4}$ S B T (old B. T.) destroy marks.

A fir, 28 ins. in diam., bears N. 17° E., 14 lks. dist.,
 marked A P T 5 N R 40 E S 36 B T

T5N40Z23

UNION COUNTY
SURVEYOR

Date Received 3/15/13

Date Filed 3/15/13

By [Signature] DEPUTY

File No. 323-2013R