CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

The corner established by General Land Office contract survey
The original notes state;
North between sections 9 and 10.
80.00 Set a basalt stone 16 x 9 x 6", 11" in ground
for corner to sections 3. 4, 9. and 10 from which a;
Pine 36" dia bears \$12.00, 190 lks dist. marked T5S R34E

S9 BT
Pine 5" dia bears \$32.0E, 56 lks dist. marked T5S R34E \$10 BT
Fir 18" dia bears N53.0E, 131 lks dist. marked T5S R34E \$3 BT
Pine 20" dia bears N38.00, 153 lks dist. marked T5S R34E \$4 BT

DIAGRA	M
T 5S	R34EWM
S 4	s 3
S 9	\$10

Description of corner evidence found:

In section 4, found 42" stump.
In section 3, found 42" stump.
In section 9, found 48" stump.
At the passer, found rock, all *** scribes.


Description of monument and accessories I established to perpetuate the original location of this corner

At the position of the corner, I set a 30° galvanized pipe with an eight inch plate welded to bottom and a bronze cap on top. The hole was back filled with stone and tamped soil.

I stamped the disk.

From the monument the original bearing trees were; (none). I established the following new bearing trees; Ponderosa Pine 12" dia, N#2°W at a distance of 12.6 ft. and scribed T5S R34E S4 BT

Ponderosa Pine 14" dia, N8°E at a distance of 26.4 ft. and sorabed



Pine 8" dia, S14°W, at a distance of 38.1 ft. and scribed T5S R34E S9 BT Ponderosa Pine 9" dia, S38°E at a distance of 7.7 ft. and scribed T5S R34E S10 BT. The distance measured to center of respective trees on level. I placed bearing tree signs on both old and new bearing trees and painted stripe around trees. I placed a steel fence post with USFS sign 54-4 attached near the corner. I placed the stone along side monument.

for record on the18 day of August	certify that the within instrument was filed	in this effice SURVEYOR
(COUNTY OFFICIAL)	Canut Cologh	Date Received
		Date Filed
26 71 00 PT (0 10 1		File No. 553-84R

Form R6-7100-57 (9/66)