


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

No previous history

G-10



Description of corner evidence found:

None

Description of monument and accessories I established to perpetuate the original location of this corner:

I set a 2½" brass cap on a 30" galv. iron pipe, and stamped as shown above, in the ground, and placed a large mound of stone around the monument.

New bearing trees:

- A pine 9" dia. bears N 07 W, 26.56 feet and scribed 1/16 S S 9 BT.
- A pine 7" dia. bears N 80 E, 22.17 feet and scribed 1/16 S S 9 BT.

I hereby certify the above corner monument was re-established as herein described in August 1978.

Witnesses:

Leonard E. Hines  
Crew Chief

P. D. Shirley  
Instrument Man

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

James H. Hambleton  
8-21-78

OREGON  
JULY 10, 1964  
JAMES H. HAMBLETON  
645

Office of..... County of.....

State of....., I hereby certify that the within instrument was filed in this office

for record on the..... day of....., 19.....

(COUNTY OFFICIAL)

(DEPUTY)

**UNION COUNTY  
SURVEYOR**

Date Received \_\_\_\_\_  
☆ GPO-798-276

Date Filed \_\_\_\_\_

By \_\_\_\_\_


File No. 555-84R

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Center - West 1/16, Sec. 9, T. 5 S., R. 34 E., W.M.

History of original corner establishment:

The Center-West 1/16, Sec. 9, T. 5 S., R. 34 E., W.M. was originally monumented by James H. Hambleton (JHH) L.S. #645, in August, 1978. JHH's record states: "I set a 2 1/2" brass cap on a 30" galv. iron pipe, and stamped as shown above, in the ground, and placed a large mound of stone around the monument."



Description of corner evidence found:

I found a 2 1/2" diam. brass cap on a 2 1/2" galvanized iron pipe, 2" above the ground, marked

T5S  
W-C-1/16  
S9  
R34E  
RLS 645 1978

From which: JHH BT's:

A stump, of a Lodgepole Pine, 8" (7") diam., bears N77°E (N80°E), a distance of 22.3 ft. (22.17 ft.), axe marks on stump, the tree lies to the northwest, scribing visible "1/16S BT", re-attached the BT & LSM signs to the tree.

A Lodgepole Pine, 12" (9") diam., bears N5 1/2°W (N7°W), a distance of 26.6 ft. (26.56 ft.), scribed "S9 BT", and Brass washer visible.

Description of monument and accessories I established to perpetuate the original location of this corner:

From the existing brass cap I established the following new BT's: A Lodgepole Pine, 10" diam., bears S88°E, a distance of 31.8 ft., scribed "CW 1/16 S9 BT", with a brass washer marked "LS 2211" nailed between the B & T, this tree was double blazed.

The brass cap is in a stone collar 3 ft. diam.

Set or reset steel fence posts: South 3 ft., and West 4.6 ft.

The intersection of road #5160 and #5160-685 bears N7°E, about 300 ft.

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*Roger Green*

OREGON  
JULY 17, 1986  
ROGER O. GREEN  
2211

Crew: Roger O. Green, Earl E. Strang  
Equipment: Kesson tape & staff compass.  
Field work: 9/17/91

Roger Green, L.S. 2211  
Wallowa-Whitman National Forest  
3502 Highway 30  
La Grande, OR 97850  
(503)963-7186

Note: Parenthetical information is Hambleton's record.

Office of..... County of.....

State of....., I hereby certify that the within instrument was filed in this office

for record on the..... day of....., 19.....

..... by .....

(COUNTY OFFICIAL)

(DEPUTY)

UNION COUNTY  
SURVEYOR  
Date Received 12/9/91 \*GPO-591-971, 1988  
Date Filed 12/12/91  
By *Gregory Black*  
File No. 040-1991/15