CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History	-1 -	Indian	 actabl	I ahmant.

Original survey by General Land Office (Contract Survey)

The original notes read; Set a basalt stone 15x12x8 ins 10 ins. in ground for cor to Sections 10,11,15 and 14 from which;

A pine 20" in diam bears N42°E 29 lks dist. marked T5S R34E S11 BT

A pine 18" in diam bears S60°E 33 lks dist marked T5S R34E S14BT; A pine 30" in diam bears S14°W 70 lks dist marked T5S R34E S15BT; A pine 30" in diam bears N10°W 67 lks dist marked T5S R34E S10BT;

5-17 DIAGRAM R34EWM T5S S10 S11 514

Description of corner evidence for

Found - A pine 25 in diam bears N42E in good condition.

A stump bears S60°E.

A down pine log bears S14.W A pine 35" in diam bears N10.W with blaze scar.

REGISTERED OREGON AND S

MAY VOELZ JAMES G. 381

> COR T5S R34E

> > S10 S11

S15 S14 ORE LIC 381

1969

nt and accessories I established to perpetuate the original location of this corner

A the position of the corner I set a 2" galvanized pipe 30" long with a bronze cap on top and 8" plate welded to bottom. The pipe set to a depth of 18" and backfilled with stone and soil.

I stamped the disk

From the monument the original bearing trees are: A pine 25" in diam bears N42°E as indicated in original notes; A pine 35" in diam bears N10°W as indicated in original notes;

I set the following new bearing trees; A pine 9 in diam bears S20°E 35 ft. dist marked T5S R34E S14BT;

A pine 16" in diam bears S75°W 21 ft. dist marked T5S R34E S15BT; I set a were pla

Trees ma

ced	on bea	aring t	rees	shoulder	hi	gh faci	ng	the corner	•	tree	signs	
rked	with	scribe	and	measured	to	center	of	respective	trees.			
•												

Office of Gounty surveyor County of Union State of Oregon I hereby certify that the within instrument was filed in for record on the 9 day of Sept 1969, at 9 g'clock P. County surveyor by	this official RVEYOR
(COUNTY OFFICIAL)	Date Received
	By