History of original corner establishments

Original survey by General Land Office (contract survey)

Set a basalt stone 20x15 x6 from which; A pine 24" in diam bears N80°E 136 lks dist marked T5S, R34E S12BT; A pine 7" in diam bears 343°E 48 lks dist marked T5S R34E A pine 36" in diam bears S37°W 126 lks dist marked T5S R34E S14 BT; A pine 12" in diam bears N80°W 186 lks dist marked T5S R34E S11BT;

J-21			
DIA	GRAM		
13B T	T5S S11 S14	R345WM S12 S13	

Description of corner evidence founds

Found stone with notches,

Found- A pine 30" in diam bears N80°E with scribe;

A 14" pine stump and log bears 543°E 48 1ks dist.

A pine 36", in diam bears \$37°W 116 1ks dist.

A 26" pine stumpbears N80°W 186 1ks dist with blage

REGISTERED
OREGON
LAND SURVEYOR

MAY 4, 1956 JAMES G. VOELZ 381

Description of monument and accessories I established to perpetuate the original location of this corner

At the position of the corner I set a 2" galvanized pipe 30" long with bronze cap on top and 8" plate welded to bottom. Pipe is set to depth of 12" and backfilled with stone and soil and raised stone monument.

COR T5S R34E

At the position of the corner the original bearing trees are.

A pine 30" in diam bears N80°E. as indicated by field notes

A pine 36" in diam; bears S37°W as indicated by field notes.

I set two new bearing trees as follows;

A pine 11" in diam bears N34°W 94.2 ft. dist marked T5S, R34E

S11 BT. A pine 23" in diam bears S30°E 26.9 ft. dist marked T5S

R34E S13BT. (distance to center of respective trees and marked by scribe)

I set a steel fence post with USFS sign 54-4 attached. USFS bearing tree signs were placed on both old and new bearing trees shoulder high and facing the corner.

Office of County Surveyor County of Union	UMIOM COUNTY SURVEYOR
State of Oregon , I hereby certify that the within instrument was filed in for record on the day of Sept 1969 clocky	this office
County Surveyor by ame (Deek Total)	Date Filed
	Ву
	File No. <u>567-84 R</u>