


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

No previous history

K-9



Description of corner evidence found:

None

Description of monument and accessories I established to perpetuate the original location of this corner:

I set a 2 1/8" brass cap on a 30" galv. iron pipe, and stamped as shown above, in the ground, and placed a large mound of stone around the monument.

New bearing trees:

- A pine 5" dia. bears N 60 W, 15.25 feet, scribed 1/16S S17 BT.
- A pine 4" dia. bears N 36 E, 21.0 feet, scribed 1/16S S16 BT.

I hereby certify the above corner monument was re-established as herein described in August 1978.

Witnesses:

Leonard E. Green
Crew Chief

R. D. Shuler
Instrument Man

REGISTERED
PROFESSIONAL
LAND SURVEYOR

James H. Hambleton
8-21-78

OREGON
JULY 10, 1983
JAMES H. HAMBLETON
645

Office of..... County of.....
State of....., I hereby certify that the within instrument was filed in this office
for record on the..... day of....., 19.....

(COUNTY OFFICIAL)

(DEPUTY)

UNION COUNTY SURVEYOR	
Date Received	_____
☆ GPO—798-276	
Date Filed	_____
By	_____
File No.	<u>569-84 R</u>