

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

K-11

History of original corner establishment:

No previous history

DIAGRAM
Cap Stamped
T 5 S
N-C-1/16
S 16
R 34 E
1978
ORLS 645

Description of corner evidence found:

None

Description of monument and accessories I established to perpetuate the original location of this corner:

I set a 2 1/2" brass cap on a 30" galv. iron pipe and stamped as shown above, in the ground, and placed a large mound of stone around the monument.

New bearing trees:

A pine 5" dia. bears N 40 W, 52.34 feet, scribed 1/16 S S 16 BT.
A pine 7" dia. bears S 35 W, 74.19 feet scribed 1/16 S S 16 BT.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

James H. Hambleton
8-21-78

OREGON
JULY 12 1909
JAMES H. HAMBLETON
645

I hereby certify the above corner monument was re-established as herein described in August 1978.

Witnesses:

Leonard E. Green
Crew Chief

L. D. Shirley
Instrument Man

Office of..... County of.....

State of....., I hereby certify that the within instrument was filed in this office

for record on the..... day of....., 19.....

..... by
(COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY
SURVEYOR
Date Received _____
Date Filed _____
By _____
File No. 570-84R