


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

K-17

History of original corner establishment:



No previous history

Description of corner evidence found:

None

Description of monument and accessories I established to perpetuate the original location of this corner:

I set a 2 1/2" brass cap in a 30" galv. iron pipe, and stamped as shown above, in the ground, and placed a large mound of stone around the monument.

New bearing trees:

- A pine 6" dia. bears N 33 W, 29.63 feet scribed 1/16S S 15 BT.
- A pine 7" dia. bears S 46 E, 41.60 feet scribed 1/16S S 14 BT.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

James H. Hambleton
8-21-78

OREGON
JULY 21, 1964
JAMES H. HAMBLETON
645

I hereby certify the above corner monument was re-established as herein described in August 1978.

Witnesses: *Leonard E. Green*
Crew Chief

L. D. Shiley
Instrument Man

Office of..... County of.....
State of....., I hereby certify that the within instrument was filed in this office
for record on the..... day of....., 19.....

..... by
(COUNTY OFFICIAL) (DEPUTY)

CLATSOP COUNTY
SURVEYOR

Received.....
☆ GPO-798-276

Date Filed.....

By.....

File No. 573-84R