## CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner was established in 1882, by Rufus S. Moore, under Gerneral Land Office Contract No. 451. Surveyor General's records state: Set a basalt stone 16" x 12" x 8", 11" in ground for the  $\frac{1}{4}$  sec. cor. marked  $\frac{1}{4}$  on west face from which: A pine 12" dia. bears S 32 W, 21 lks. dist. marked AS BT. A fir 24" dia. bears N 04 E, 33 lks. dist. marked ±S BT.

Description of corner evidence found:

At the assumed corner location I found a basalt stone  $16^n$  x  $12^n$  x  $8^n$  lying flush with the surface and with  $\frac{1}{4}$  marked on the west face, from

A pine stump approx. 20" dia. bears S 32 W, 21 lks. dist.; no blaze or scribing.

A badly rotted fir lying on the ground, base bears N 04 E, 33 lks. dist.; portions of scribing are visible.

Description of monument and accessories I established to perpetuate the original location of this corner:

As the evidence in the vicinity of the corner agrees with the GLO original record, at the location of the found stone, I set a 21 brass cap on a 30" galv. iron pipe, and being stamped as shown above, with a large mound of stone and dirt around the monument.

New bearing trees: A fir 5" dia. bears N 85 W, 47.0 feet scribed  $\frac{1}{4}$ S S 17 BT. A tamarack 9" dia. bears S 25 E, 46.5 feet scribed  $\frac{1}{4}$ S S 16 BT.

REGISTERED PROFESSIONAL	
LAND SURVEYOR	
8-21-78	ر
JAMES H. HAMBLETON.	

I hereby certify the above corner monument was re-established as herein described in August 1978.

Grew Chief Witnesses:

Instrument Man

Office of	unty of		
, I nereby certify that t	ho within in a	n this office	
	10		
(COUNTY OFFICIAL)	(DEPUTY)		SURVEYOR
6-7100-57 (9/71)			
•			Roceived A gpo-798-276
		Dat	e Filed

F