

54-69A

47


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

L-17

History of original corner establishment:

Original survey by General Land Office contract survey.

The original notes read; Set a basalt stone 2 1/2 x 8 x 3 marked 1/4 on face from which;
A pine 4" in diam bears S42°E 14 lks dist Marked 1/4 SBT;
A pine 6" in diam bears S44°E 71 lks dist marked 1/4 SBT/



Description of corner evidence found:

Found a log 10" in diam with scribe at S44°E
no other evidence was found.


REGISTERED
OREGON
LAND SURVEYOR

James G. Voelz
MAY 4, 1956
JAMES G. VOELZ
381

Description of monument and accessories I established to perpetuate the original location of this corner

At the position of the corner I set a 2" galvanized pipe 30" long with bronze cap on top and 8" plate welded to bottom. The pipe set to a depth of 23" and backfilled with stone and soil

I stamped the disk



From the monument, the original bearing trees are none.

I set two new trees as follows;

A black pine 14" in diam bears N64°E 19 ft dist. marked 1/4 SBT;

A black pine 11" in diam bears N82°W 11.6 ft dist marked 1/4 SBT

(Distance measured to center of trees and marked with a scribe)

I set a steel fence post with USFS sign 54-4 attached. National Forest boundary signs were placed on the post indicating National Forest land to northeast and southwest. USFS bearing tree signs were placed on the bearing trees shoulder high facing the corner.

Office of County SURVEYOR County of Union
State of Oregon , I hereby certify that the within instrument was filed in this office
for record on the ..10.. day of ..Sept....., 1969, at 10 o'clock P. m. (signed)
..... Co surveyor by *James G. Voelz*
(COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY
SURVEYOR

Date Received _____

Date Filed _____

By _____

File No. 578-84 R