


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

L-19

History of original corner establishment:

No previous history



Description of corner evidence found:

None

Description of monument and accessories I established to perpetuate the original location of this corner:

I set a 2 1/2" brass cap in a 30" galv. iron pipe, and stamped as shown above, in the ground, and placed a large mound of stone around the monument.

New bearing trees:

A pine 7" dia. bears N 17 W, 35.42 feet scribed 1/4 S S 14 BT.

A pine 5" dia. bears S 13 W, 17.63 feet scribed 1/4 S S 14 BT.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

James H. Hambleton
8-21-78

OREGON
JULY 10, 1904
JAMES H. HAMBLETON
645

I hereby certify the above corner monument was re-established as herein described in August 1978.

Witnesses: *Leonard E. Shuman*
Crew Chief

L. D. Shirley
Instrument Man

Office of..... County of.....

State of....., I hereby certify that the within instrument was filed in this office

for record on the..... day of....., 19.....

..... by
(COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY SURVEYOR	
Date Received	_____
* GPO-798-276	
Date Filed	_____
By	_____
File No.	<u>579-84R</u>