


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

L-23

History of original corner establishment:



No previous history

Description of corner evidence found:

None

Description of monument and accessories I established to perpetuate the original location of this corner:

I set a 2 1/2" brass cap in a 30" galv. iron pipe, and stamped as shown above, in the ground, and placed a large mound of stone around the monument.

New bearing trees:

A pine 9" dia. bears S 42 W, 47.17 feet scribed C 1/4 S 13 BT.
A fir 9" dia. bears N 27 W, 44.59 feet scribed C 1/4 S 13 BT.

I hereby certify the above corner monument was re-established as herein described in August 1978.

REGISTERED PROFESSIONAL LAND SURVEYOR

James H. Hambleton
8-21-78

OREGON JULY 10, 1964 JAMES H. HAMBLETON 645

Witnesses:

Leonard E. Strem
Crew Chief

L. H. Shirley
Instrument Man

Office of..... County of.....
State of....., I hereby certify that the within instrument was filed in this office
for record on the..... day of....., 19.....

(COUNTY OFFICIAL)

(DEPUTY)

Form R6-7100-57 (9/71)

UNION COUNTY SURVEYOR
Date Received _____
☆ GPO—798-276
Date Filed _____
By _____
File No <u>582-84 R</u>