


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

m-19

History of original corner establishment:

No previous history



Description of corner evidence found:

None

Description of monument and accessories I established to perpetuate the original location of this corner:

I set a 2 1/2" brass cap in a 30" galv. iron pipe, and stamped as shown above, in the ground, and placed a large mound of stone around the monument.

New bearing trees:

A pine 5" dia. bears N 10 W, 36.0 feet scribed 1/16S S 1/4 BT.

A pine 6" dia. bears S 80 E, 49.75 feet scribed 1/16S S 1/4 BT.

REGISTERED PROFESSIONAL LAND SURVEYOR

James H. Hambleton
8-21-78

OREGON JULY 10, 1964 JAMES H. HAMBLETON 645
--

I hereby certify the above corner monument was re-established as herein described in August 1978.

Witnesses:

Leonard E. Green
Crew Chief

L. D. Shibley
Instrument Man

Office of..... County of.....
State of....., I hereby certify that the within instrument was filed in this office
for record on the..... day of....., 19.....

..... by
(COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY SURVEYOR
Received _____
☆ GPO—798-276
Date Filed _____
By _____
File No. 585-84R