

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

m-23

History of original corner establishment:

No previous history

DIAGRAM
Cap Stamped
T 5 S
S-C-1/16
S 13
R 34 E
1978
ORLS 645

Description of corner evidence found:

None

Description of monument and accessories established to perpetuate the original location of this corner:

I set a 2 1/2" brass cap in a 30" galv. iron pipe, and stamped as shown above, in the ground, and placed a large mound of stone around the monument.

New bearing trees:

A pine 9" dia. bears N 53 W, 16.75 feet, scribed 1/16S S 13 BT.
A pine 7" dia. bears S 14 W, 31.67 feet, scribed 1/16S S 13 BT.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

James H. Hambleton
8-21-78

OREGON
JULY 19, 1954
JAMES H. HAMBLETON
645

I hereby certify the above corner monument was re-established as herein described in August 1978.

Witnesses: *Leonard E. Green*
Crew Chief

P. D. Shiley
Instrument Man

Office of..... County of.....

State of....., I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19.....

..... by
(COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY
SURVEYOR
Date Received.....
☆ GPO—798-276
Date Filed.....
By.....
File No. 588-84R