CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner was established in 1882, by Rufus S. Moore, under General Land Office Contract No. 451. Surveyor General's records state: Set a basalt stone 16 x 12 x 4, 11" in ground for $\frac{1}{4}$ sec. Cor. marked $\frac{1}{4}$ on N face from which:
A fir 12" dia. bears N 43 W, 39 lks. dist. marked

fir 7^{m} dia. bears S 12 E, 10 lks, dist. marked $\frac{1}{4}$ S BT.

DIAGRAM Cap Stamped T 5 S S 16 S 21 R 34 E 1978 ORLS 645

Description of corner evidence found:

At assumed corner location I found a basalt stone 16 x 12 x 4 lying flat on the ground and marked $\frac{1}{4}$ on the side facing down with a small mound of stone alongside from which:

A fir 22" dia. bears N 43 W, 39 lks. dist. with a portion of a healed blaze being opened at some previous time exposing a portion of the scribing; the tree is alive and in good condition.

A fir 15" dia. bears S 12 E, 10 lks. dist. with the blaze healed over completely.

Description of monument and accessories I established to perpetuate the original location of this corner:

As the evidence in the vicinity of the corner agrees with the GLO original record, at the location of the stone, I set a $2\frac{1}{2}$ brass cap on a 30 galv. iron pipe, and being stamped as shown above, I placed the 16 x 12 x 4 basalt stone upside down in the hole along the west side of the monument and buried both in a large mound of stone and dirt.

I set no new bearing trees as it was not necessary.

for record on the...... day of...... , 19.....

(COUNTY OFFICIAL)

..... by

REGISTERED PROFESSIONAL LAND SURVEYOR OREGON DEGON JAMES H. HAMBLETON 645	I hereby certify the above corner monument was re-established as herei described in August 1978. Witnesses: Crew Chief Instrument Man

(DEPUTY)

Form R6-7100-57 (9/71)

The Received ☆ GPO--798-276 Date Filed_

File No. 590-84 R

umon county

SURVEYOR