CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner was established in 1882, by Rufus S. Moore, under General Land Office Contract No. 451.

Surveyor General's records state: Set a post 4 ft. long 4" square, 24" in ground for corner to Sec's. 15, 16, 21 & 22 marked T 5 S S 15 on NE, R 34 E S 16 on NW, S 21 on SW and S 22 on the SE faces with 3 notches on the S and E edges from which:

A pine 8" dia. bears S 17 W 54 lks. dist. marked

N-13
DIAGRAM Cap Stamped T 5 S
s 16 S 15 S 21 S 22 R 34 E 1978 ORLS 645

on NW, S 21 on SW and S 22 on the SE faces with 3
notches on the S and E edges from which:

A pine 8" dia. bears S 17 W 54 lks. dist. marked

T 5 S R 34 E S 21 BT.

A fir 5" dia. bears S 32 W 15 lks. dist. marked T 5 S R 34 E S 22 BT.

A tamarack 6" dia. bears N 23 W 43 lks. dist. marked T 5 S R 34 E S 16 BT.

A pine 5" dia. bears N 47 E 49 lks. dist. marked T 5 S R 34 E S 15 BT.

Description of corner evidence found:

At assumed corner location I found no trace of the original section corner, nor any evidence of the bearing trees, as there was evidence of a fire in the early 1900's through this area of which destroyed all evidence of the original corner.

Description of monument and accessories I established to perpetuate the original location of this corner:

Assuming this corner to be lost, I then used double proportioning measurements to re-establish the section corner, thus I set a $2\frac{1}{2}$ brass cap on a 30" galv. iron pipe, and being stamped as shown above, with a large mound of stone and dirt around, and of which buried the monument.

New bearing trees:
A tamarack 9" dia. bears N 70 E, 21.42 feet scribed T 5 S R 34 E S 15 BT.
A tamarack 11" dia. bears N 38 W, 33.67 feet scribed T 5 S R 34 E S 16 BT,
A tamarack 8" dia. bears S 22 W, 35.9 feet scribed T 5 S R 34 E S 21 BT.
A tamarack 12" dia. bears S 10 E, 27.67 feet scribed T 5 S R 34 E S 22 BT.

REGISTERED
PROFESSIONAL
LAND SURVEYOR
() () () () ()
Vans Hambledon
8-21-78
OREGOTAL
JAMES H. HAMBLETON
645
The same of the sa

I hereby certify the above corner monument was re-established as herein described in August 1978.

Witnesses:

Crew Chief

Crew Chief

Milling

Instrument/Man

State of, hereby certify th	at the within instrument was filed in	this office
for record on the day of	on the day of , 19	
by (COUNTY OFFICIAL)	(DEPUTY)	SURVEYOR
form R6-7100-57 (9/71)		to Rockyond 100 270
		Date Filed
		Ву
		File No. 591-841