CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner was established in 1882, by Rufus S. Moore, under General Land Office Contract No. 451.

Surveyor General'serecords state: Set a basalt stone 18 x 12 x 4, 12" in the ground for \(\frac{1}{4}\) sec. cor. marked \(\frac{1}{4}\) on N face from which:

A pine 4" dia. bears N 58 E, 21 lks. dist. marked \(\frac{1}{4}\)S BT.

A pine 15" dia. bears S 19 E, 45 lks. dist. marked \(\frac{1}{4}\)S BT.

 $\frac{1}{4}S$ BT.

N-19
DIAGRAM
Cap Stamped T 5 S
ΤζS
2 4
<u>s il.</u> S 23
<u> </u>
R 34 E
1978 ORLS 614
URLS ALL

Description of corner evidence found:

At assumed corner location I found a basalt stone 18 x 12 x 4 with marked on the north face and 4 notches at the opposite end of the stone, stone setting upright about 10" in the ground. There was no trace of the bearing trees as there was evidence of a fire in the area in the early 1900's.

Description of monument and accessories I established to perpetuate the original location of this corner:

As the evidence in the vicinity of the corner agrees with the GLO original record, at the location of the stone I set a $2\frac{1}{2}$ " brass cap on a 30" galv. iron pipe and being stamped as shown above, placing the 18 x 12 x 4" stone upside down in the hole alongside the monument and buried both in a large mound of stone.

New bearing trees: A pine 6" dia. bears N 40 E, 23.29 feet scribed $\frac{1}{4}$ S S 14 BT. A pine 8" dia. bears S 31 E, 29.0 feet scribed $\frac{1}{4}$ S S 23 BT.

REGISTERED PROFESSIONAL LAND SURVEYOR
Tames HHamb Str
OREGON JAMES H. HAMELITON 645

I hereby certify the above corner monument was re-established as herein described in August 1978.

Witnesses:

Instrument Man

File No 594-84R

Office of	County of	
for record on the day of by	Vision const	
(COUNTY OFFICIAL)	(DEPUTY)	30% 62 8 69%
Form R6-7100-57 (9/71)		Date Received_ ☆ GPO —798-276
		Date Filed