


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:
None

Index File No. 0-23



Description of corner evidence found:
No monument or evidence found.

Description of monument and accessories established to perpetuate the original location of this corner:

Set 2.5" aluminum cap on 2 3/8"x30" aluminum pipe rising 12" above ground. Cap is stamped:

Set steel fence post 3.0 ft. west of corner.

BT's:

- A 6" L. Pine bears S8°E, 19.3 ft., blazed and scribed: CN 1/16 S24 BT.
- A 5" L. Pine bears S69°W, 35.4 ft., blazed and scribed: CN 1/16 S24 BT.

T5S R34E
C
N1/16 | S 24
C
RLS 1844
1984

Brass LS 1844 disc in lower end of blaze. Painted blazes and attached signs as per Standard Specifications for Cadastral Surveys, USFS Region 6, March 1982.

Compass Declination: 19 3/4°E

Witness: Duane Scott

Corner is found at 20 ft. elevation above Fly Creek on end of small northeast-to-southwest ridge, 700 ft. south of Fly Creek. Road 5160-544 runs on north side of creek.

I hereby certify the above described corner monument and/or accessories was established as described on June 23, 1984.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

David E. Scott

OREGON
JULY 13, 1979
DAVID E. SCOTT
1844

Office of..... County of.....
 State of....., I hereby certify that the within instrument was filed in this office
 for record on the..... day of....., 19.....
 by
 (COUNTY OFFICIAL) (DEPUTY)

**UNION COUNTY
SURVEYOR**

Date Received 10-17-84

Date Filed 10-24-84

By G. LANGLITZ, DEPUTY

File No. 953-84R