


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. R-19

History of original corner establishment:

The original subdivision of T5S, R34E was by Rufus S. Moore under Contract No. 451, approved Feb. 1, 1884. He set a post, from which a 7" Pine bears N13°W, 5 lks. and a 5" Pine bears S5°W, 7 lks.



Description of corner evidence found:

No corner monument found. Found one 7" Pine, dead and down, bearing N13°W, 3.3 ft. from corner, scribed (1/4 S 23).

Description of monument and accessories I established to perpetuate the original location of this corner:

Set 2.5" aluminum cap on 2 3/8"x30" aluminum pipe rising 6" above ground. Cap is stamped:  
Set steel fence post 3.0 ft. north of corner.

T5S R34E  
1/4  $\frac{S23}{S26}$   
RLS 1844  
1984

New BT's:

A 6" Fir bears N20°E, 4.6 ft., blazed & scribed: 1/4 S23 BT.  
An 8" Tamarack bears S29 1/4°E, 36.3 ft., blazed and scribed:  
1/4 S26 BT.


Brass LS 1844 disc in lower end of blaze. Painted blazes and attached signs as per Standard Specifications for Cadastral Surveys, USFS Region 6, March 1982.

Compass Declination: 19 3/4°E

Witness: Duane Scott

Corner is found on slight north slope in heavy young lodgepole and tamarack timber. Nearest roads are east or west 1/2 mile near section corners. Fastest walk from east.

I hereby certify the above described corner monument and/or accessories was established as described on June 21, 1984.



Office of..... County of.....  
State of....., I hereby certify that the within instrument was filed in this office  
for record on the..... day of....., 19.....  
..... by .....  
(COUNTY OFFICIAL) (DEPUTY)

|  |
|--|
| <b>UNION COUNTY SURVEYOR</b>                             |
| Date Received <u>10-17-84</u>                            |
| Date Filed <u>10-24-84</u><br><small>GPO-798-276</small> |
| By <u>G. LANGLITZ DEPUTY</u>                             |
| File No. <u>961-84 R</u>                                 |