## CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

The original subdivision of T5S, R34E was by Rufus S. Moore under Contract No. 451, approved Feb. 1, 1884. Set stone 12x10x7, from which a 7" Pine bears N47°E, 94 lks., a 44" Pine bears N30°W, 60 lks., a 36" Pine bears S18°W, 127 lks., and an 8" Fir bears S36°E, 107 lks.

Index File No. R-	21
DIAGRAM	
T5S R34E	
23   24 26   25	

## Description of corner evidence found:

Found stone 12x10x7, 8" in ground, 2 notches on south, 1 notch on east.

Bearing trees found:

A 15" Fir bears S33 1/4°E, 70.6 ft., healed blaze.

A 36" P. Pine bears S21 3/4°W, 85.0 ft., healed blaze.

A 44" P. Pine, dead & down, bears N23.5°W, 40.0 ft., no marks.

Description of monument and accessories I established to perpetuate the original location of this corner:

T5S R34E S23 S24 S26 S25

At location of stone, set 2.5" aluminum cap on 2 3/8"x30" aluminum pipe 12" above ground in rock and dirt mound. Cap is stamped:

RLS 1844 1984

Set steel fence post 3.0 ft. north.

New BT's:

A 7" P. Pine bears N18 3/4°W, 49.3 ft., blazed & scribed: T5S R34E S23 BT.

A 7" Fir bears N29 1/4°E, 52.3 ft., blazed & scribed: T5S R34E S24 BT.

Brass LS 1844 disc in lower end of blaze. Painted blazes and attached signs as per Standard Specifications for Cadastral Surveys, USFS Region 6, March 1982.

Compass Declination: 19 3/4°E

Witness: Duane Scott

Corner is found 200 ft. east of Road 5160-196. Location poster on 8" P. Pine east side road. northeast corner in large clearing.

I hereby certify the above described corner monument and/or accessories was established as described in June of 1984.

PROFESSIONAL LAND SURVEYOR

CREGON JULY 13, 1979 DAVID E. SCOFT 1844

(COUNTY OFFICIAL)

Form R6-7100-57 (9/71)

Date Received 10-17-84
10-24-84
Date Filed GPO-798-278

By G. LANGLITZ DEPUTY
File No. 962-84 R