


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. U-18

History of original corner establishment:

None



Description of corner evidence found:

No corner monument of other official accessories found.

Description of monument and accessories established to perpetuate the original location of this corner:

Cap is stamped;

Set 2.5" Brass Cap on 2 3/8"x30" aluminum pipe rising 19" above ground in mound of dirt and rock. Set steel fence post 3.0 ft. east of corner.

T5S R34E  
SW 1/16•S26  
RLS 1844  
1984

New BT's:

- A 7" P. Pine bears N40 1/4°E, 47.3 ft., blazed & scribed: SW 1/16 S26 BT.
- A 7" P. Pine bears S8 1/4°W, 22.2 ft., blazed & scribed: SW 1/16 S26 BT.


Brass LS 1844 disc in lower end of blazes. Painted blazes and attached signs as per Standard Specifications for Cadastral Surveys, USFS Region 6, March 1982.

Compass Declination: 19 3/4°E

Witness: Duane Scott

Corner is found 2.0 ft. south of east-west fence; 300 ft. from top of hill to East; 800 ft. south of Toad 5160-090.

I hereby certify the above described corner monument and/or accessories was established as described on June 25, 1984.



Office of..... County of.....  
State of..... I hereby certify that the within instrument was filed in this office  
for record on the..... day of....., 19.....

(COUNTY OFFICIAL)

(DEPUTY)

**UNION COUNTY SURVEYOR**

Date Received 10-17-84

Date Filed 10-24-84  
GPO-798-276

By G. LANGLITZ, Deputy

File No. 969-84 R