


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. Z-17

History of original corner establishment:

The original subdivision of T5S, R34E was by Rufus S. Moore under Contract No. 451, approved Feb. 1, 1884. He found a 4" diam. Pine tree for Standard Corner, from which a 22" Tamarack bears N39°W, 36 lks and a 3" Pine bears N70°E, 22 lks. The township line between T5S and T6S had been surveyed by J. Cooper under Contract No. 397, approved April 5, 1882.



Description of corner evidence found:

No corner monument found. Found 22" tamarack, bearing N39°W, 24.7 ft. from corner to center of tree, 23.8 ft. to blaze.

Description of monument and accessories established to perpetuate the original location of this corner:

Set 2.5" aluminum cap on 2 3/8"x30" aluminum pipe rising 7" above ground. Cap is stamped:

Set steel fence post 3.0 ft. north of corner.

New BT: An 8" Fir bears N76.5°E, 52.4 ft., blazed & scribed: SC T5S R34E S35 BT.

SC	
T5S	R34E
S34	S35
RLS 1844	
1984	

Brass LS 1844 disc in lower end of blaze. Painted blazes and attached signs as per Standard Specifications for Cadastral Surveys, USFS Region 6, March 1982.

Compass Declination: 19 3/4°E

Witness: Duane Scott

Corner is found near north edge of large flat on top ridge in heavy timber and brush. 75 ft. north station 35+00 on proposed road 5160-170 extension.

I hereby certify the above described corner monument and/or accessories was established as described on June 20, 1984.

*David E. Scott*

DEPUTY SURVEYOR

Office of..... County of.....  
 State of....., I hereby certify that the within instrument was filed in this office  
 for record on the..... day of....., 19.....  
 ..... by .....  
 (COUNTY OFFICIAL) (DEPUTY)

**UNION COUNTY SURVEYOR**

---

Date Received 10-17-84

Date Filed 10-24-84

By G. LANGLITZ, DEPUTY

File No. 986-84R