


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. Z-19

History of original corner establishment:



The original subdivision of T5S, R34E was by Rufus S. Moore under Contract No. 451, approved Feb. 1, 1884. Found a post, from which a 4" Pine bears N40°E, 40 lks. and a 12" Pine bears N59°W, 59 lks. The township line between T5S and T6S had been surveyed by J. Cooper under Contract No. 397, approved April 5, 1882.

Description of corner evidence found:

No corner monument found.

Found one bearing tree: a 14" L. Pine stump 40" high, bearing N40°E 26.6 ft. from corner location, scribed: (SC) (1/4 S).

Description of monument and accessories established to perpetuate the original location of this corner:

Set 2.5" aluminum cap on 2 3/8"x30" aluminum pipe rising 7" above ground. Cap stamped:

SC
T5S R34E

Set steel fence post with sign 54-4, 3 ft. north.

1/4, S35

RLS 1844
1984

New BT's:

A 5" Fir bears N68 3/4°E, 32.9 ft., blazed and scribed: SC 1/4 S35 BT.

An 8" Fir bears N33°W, 9.0 ft., blazed and scribed: SC 1/4 S35 BT.


Brass LSL844 disc in lower end of blazes. Painted blazes and attached signs as per Standard Specifications for Cadastral Surveys, USFS Region 6, March, 1982. Set steel fence post 3 ft. north.

Compass Declination: 19 3/4°E

Witness: Duane Scott

Corner is found 30 ft. north of Road 5160-170, 0.5 miles from Road 5160.

I hereby certify the above described corner monument and/or accessories was established as described in June of 1984.



Office of..... County of.....

State of....., I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19.....

..... by (COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY SURVEYOR
Date Received <u>10-17-84</u>
Date Filed <u>10-24-84</u>
By <u>G. LANGLITZ, DEPUTY</u>
File No. <u>987-84 R</u>