History of original corner establishment:

Corner originally established by Jacob C. Cooper under GLO contract number 397 dated July 1, 1881. Surveyor General

Set a post 4 ft long 4 ins square for cor to secs 1-2-35 and 36 from which:


A fir 4 in dia bears $N67^{\circ}E$ 6 1ks dist A pine 5 ins dia bears $S31^{\circ}E$ 20 1ks dist A fir 12 ins dia bears $S25^{\circ}W$ 30 1ks dist

No record of subsequent remonumentation found

Description of corner evidence found:

Found marked post in stone mound, standing with scribes visible

Found rotted remains of the Southeast BT dead down and loose on the ground with scribing visible, approximately \$20°E 8 ft. Found rotted remains of the Southwest BT dead and down with scribes visible at record bearing and distance from the post



Description of monument and accessories I established to perpetuate the

original location of this corner: In place of post, I set a 2½'x30" aluminum pipe with aluminum cap marked as shown, 19 inches in the ground, from which:

New BTs

A 11 inch diameter Red Fir bears N51°E 33.56 feet marked T4S R35E S36 BT A 12 inch diameter Red Fir bears S61°E 26.92 feet marked T5S R35E S1 BT

A 13 inch diameter Red Fir bears S30°W 39.24 feet marked T5S R35E S2 BT A 21 inch diameter double bole tamarack bears N40°W 58.70 feet

marked T4S R35E S35 BT

Raised mound of stone around monument Removed post to avoid confusion (impractical to bury)

Set steel fencepost approximately 5 feet North with 54-4 sign

GRIFFITH T4S R35E s 35 | s 36 S 2 S 1 T5S 1986 OPLS 6ªª

PROFESSIONAL AND SURVEYOR OREGON JULY 10, 1964 **DUANE I. GRIFFITH**

REGISTERED

I used a steel tape and magnetic compass in the establishment of these accessories. I used 200East magnetic declination and the distances are to a 50d spike driven at the root crown on the right side of the BT. attached a brass washer marked OPLS 644 by the BT blaze of the new BTs.

Office of	County of
	tify that the within instrument was filed in this office
for record on the day of	, 19
	by
	(DEPLITY)

Form R6-7100-57 (9/71)

☆U.S. GOVERNMENT PRINTING OFFICE - 1983-793-276