


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. P-25¹

History of original corner establishment:

The original range line between, R34E and R35E was by J. Cooper, under Contract No. 3971, approved April 15, 1882. He set a post, from which a 5" Pine bears S57°W, 8 lks. and a 6" Pine bears S81°E, 9 lks.



Description of corner evidence found:
No monument or evidence found.

Description of monument and accessories established to perpetuate the original location of this corner:

Set 2.5" aluminum cap on 2 3/8"x30" aluminum pipe rising 14" above ground in mound of rock and dirt. Set steel post 3.0 ft. west. Corner set by proportion.

T5S
1/4
R34E R35E
S24 1/2 S19
RLS 1844
1984

New BT's:

- A 6" L. Pine bears S48.5°W, 19.9 ft., blazed and scribed: 1/4 S24 BT.
- A 6" L. Pine bears S30°E, 20.0 ft., blazed and scribed: 1/4 S19 BT.

Brass LS 1844 disc in lower end of blaze. Painted blazes and attached signs as per Standard Specifications for Cadastral Surveys, USFS Region 6, March 1982.

Compass Declination: 19 3/4°E

Witness: Duane Scott

Corner is found 46 ft. west of north-south fence, on north slope 1300 ft. south of Fly Creek. Take Road 5160-540 to Fly Creek, then dirt track east along creek to fence. Walk south to corner.

I hereby certify the above described corner monument and/or accessories was established as described on June 22, 1984.

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

David E. Scott

OREGON
JULY 13, 1979
DAVID E. SCOTT
1844

Office of..... County of.....
State of..... I hereby certify that the within instrument was filed in this office
for record on the..... day of....., 19.....

**UNION COUNTY
SURVEYOR**

..... by
(COUNTY OFFICIAL) (DEPUTY)

Date Received	<u>10-17-84</u>
Date Filed	<u>10-24-84</u>
By	<u>G. LANGLITZ, Deputy</u>
File No.	<u>958-84 R</u>