


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No R-25

History of original corner establishment:

The original range line between R34E and R35E was by J. Cooper under Contract No. 397, approved April 15, 1882. He set a post, from which an 8" Pine bears S26°E, 42 lks., a 6" Pine bears S17°W, 53 lks., and a 25" Pine bears N20°W, 95 lks.



Description of corner evidence found:

No monument or evidence found.

Description of monument and accessories established to perpetuate the original location of this corner:

Set 2.5" aluminum cap on 2 3/8"x30" aluminum pipe rising 18" above ground in mound of rock and earth. Cap is stamped:
Set steel fence post 3.0 FT NORTH
Corner set by proportion.
New BT's:

T5S
R34E R35E
S24 S19
S25 S30
RLS 1844
1984

- 6" L. Pine bears N8 3/4°W, 37.4 ft., blazed & scribed; T5S R34E S24 BT.
- 5" L. Pine bears S16 1/4°W, 19.2 ft., blazed & scribed; T5S R34E S25 BT.
- 5.5" L. Pine " N81.5°E, 19.9 ft., blazed & scribed; T5S R35E S19 BT.
- 5.5" L. Pine " S56°E, 26.1 ft., blazed & scribed; T5S R35E S30 BT.

Brass LS 1844 disc in lower end of blaze. Painted blazes and attached signs as per Standard Specifications for Cadastral Surveys, USFS Region 6, March 1982.

Compass Declination: 19 3/4°E Witness: Duane Scott

Corner is found 75 ft. west of north-south fence 600 ft. north of Lookout Creek. From Road 5166-065 east to fence line, then north across Lookout Creek to corner.

I hereby certify the above described corner monument and/or accessories was established as described on June 22, 1984.

REGISTERED PROFESSIONAL LAND SURVEYOR
--

<i>David E. Scott</i>
OREGON JULY 13, 1979 DAVID E. SCOTT 1844

Office of..... County of.....
 State of..... I hereby certify that the within instrument was filed in this office
 for record on the..... day of....., 19.....
 by.....
 (COUNTY OFFICIAL)

UNION COUNTY SURVEYOR
(DEPUTY)
Date Received <u>10-17-84</u>
Date Filed <u>10-24-84</u>
By <u>G. LANGLITZ, DEPUTY</u>
File No. <u>964-84R</u>