


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. R-11

History of original corner establishment:

In 1882, under Contract No. 451, Rufus S. Moore set a stone 12x12x5, from which an 18" Pine bears N48°W, 54 lks. and a 12" Pine bears S75°W, 53 lks.



Description of corner evidence found:

No corner monument found. Found a 24" Pine stump, dead and down, bears N48°W, 54 lks. marked "1/4 S BT." Found a root crown, with no marks, bears S75°W, 53 lks.

Description of monument and accessories I established to perpetuate the original location of this corner:

Cap is stamped:

Corner set by evidence.
Set 2.5"x30" aluminum capped aluminum pipe rising 10" above ground in mound. Set steel fence post 3.0 ft. north of corner.

T5S R35E
1/4 S 21
S 28
RLS 1844
1985

New BT's:
12.5" P. Pine bears N13.5°E, 16.1 ft.,
blazed and scribed: 1/4 S21 BT.
9" P. Pine bears S13.5°W, 18.6 ft.,
blazed and scribed: 1/4 S28 BT.

Painted blazes and attached signs as per Standard Specifications for Cadastral Surveys, USFS Region 6, March 1982. Brass disk stamped "LS 1844" nailed to lower end of blazes.

Corner is on south slope in open timber, it has been logged and later thinned. Follow Road 5155 to location poster on 6" Fir, 0.1 mile past Road 5155-060, corner is 800' north.

Compass Declination: 19 1/2°E
Witness: Bernie Sutton

I hereby certify the above described corner monument and/or accessories was established as described on May 5, 1985.



Office of..... County of.....

State of....., I hereby certify that the within instrument was filed in this office

for record on the..... day of....., 19.....

..... by

(COUNTY OFFICIAL)

(DEPUTY)

UNION COUNTY SURVEYOR
Date Received 9-18-85
★ GPO—798-274
Date Filed 9-23-85
By G. LANGLITZ, DEPUTY
File No. 62-85R