


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. R-13

History of original corner establishment:

In 1882, under Contract No. 451, Rufus S. Moore set a post, from which a 7" Pine bears S38°E, 42 lks., another 7" Pine bears S30°W, 55 lks., a 20" Fir bears N52°W, 75 lks., and an 18" Pine bears N12°E, 72 lks.



Description of corner evidence found:

No corner monument or evidence found.


From set corner, 30 ft. west, found 10" L. Pine with chopped blaze and location poster dated 1/3/41, no scribing.

Description of monument and accessories established to perpetuate the original location of this corner:

Cap is stamped: T5S R35E

Corner set by double proportioning.

Set 2. 5"x30" aluminum capped aluminum pipe rising 6" above ground. Set steel fence post 3.0 ft. north of corner.



RLS 1844
1985

New BT's:

- 6.5" W. Larch bears S25°E, 6.4 ft., blazed & scribed: T5S R35E S27 BT.
- 6.5" W Larch bears S53.5°W, 16.1 ft., blazed & scribed: T5S R35E S28 BT
- 7" W. Larch bears N31 3/4°W, 55.1 ft., blazed & scribed: T5S R35E S21 BT.
- 8.5" W. Larch bears N31°E, 13.8 ft., blazed & scribed: T5S R35E S22 BT.

Painted blazes and attached signs as per Standard Specifications for Cadastral Surveys, USFS Region 6, March 1982. Brass disk stamped "LS 1844" nailed to lower end of blazes.

Corner is on the east side of a draw 12 ft. west of Road 5155-039 and 1200 ft. north of Road 5155.

Compass Declination: 19 1/2°E

Witness: Bernie Sutton

I hereby certify the above described corner monument and/or accessories was established as described on April 12, 1985.



Office of..... County of.....

State of....., I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19.....

..... by
(COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY SURVEYOR
Date Received <u>9-18-85</u>
Date Filed <u>9-23-85</u>
By <u>G. LANGLITZ DEPUTY</u>
File No. <u>63-85 R</u>