CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishments

Original survey by General Land Office contradt survey 1882

The original notes read; Set a basalt stone 16x9x7 ins from which A pine 7" in diam bears N96°W 60 lks dist marked R358 S23BT; A pine 4" in diam bears S85°W 33 lks dist marked S26BT; A pine 4" in diam bears S27°E 277 lks dist marked S25BT; No other trees in limits.

R-21		
DIAGRAM T5S R35EV	νM	
S2 <u>3 S24</u> S26 S25		

Possibilen of corner evidence found:
Found marked stone.
In section 26 found slab with scribe;
In section 25 found slab with scribe;
In section 24 found slab with scribe;

OREGON LAND FIRVEYOR

MAY 4, 1956

JAMES G. VOELZ

381

REGISTERED

Description of monument and accessories I established to perpetuate the original location of this corner

AT the position of the rock I set a 2" galvanized pipe 30"long with bronze cap on top and 8" plate welded to bottom. The pipe set to a depth of 30" and back filled with stone and soil. I placed the stone on south side of pipe.

I stamped the disk

COR T5S R35E S23 S24 A26 S25 CRE LIC 381 1969

From the monument the following new bearing trees are;

A pine 22" in diam bears N70°E 136.9 ft. marked T5S R35E S24BT;

A pine 19" in diam bears S50°E 85 ft. dist marked T5S R35E S25/BT;

A pine 13" in diam bears S63°W 24.6 ft. dist marked T5S R35E S25BT;

A pine 18" in diam bears N23°W51 ft. dist marked T5S R35E S23BT;

Distance measured to center of trees and marked with ascribe.

I set a steel fence post with USFS sign 54-4 attached. National Forest boundary sign was placed on the post indicating National Forest land to North. USFS bearing tree signs were placed on the bearing trees shoulder high facing the corner.

		UNION COUNTY
Office of	rtify that the within instrument was fill	SURVEYOR
for record on the12 day of Sept Co surveyor	19 69, m.?, orgloca	
(COUNTY OFFICIAL)	HOSSHTVA	Date Filed
		Ву
		File No. 610 - 81 B