


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. V-11

History of original corner establishment:

In 1882, under GLO Contract 451, Rufus S. Moore set a post from which a 6" Pine bears N31°W, 34 lks. and a 9" Pine bears S34°W, 11 lks.



Description of corner evidence found:

No corner monument or other evidence found.

Description of monument and accessories established to perpetuate the original location of this corner:

Cap is stamped:

Corner set by single proportioning.
Set a 2.5"x30" aluminum capped aluminum pipe rising 6" above ground. Set steel fence post 3.0 ft. north of corner.

T5S R35E
 $\frac{1/4 + 28}{33}$
 RLS 1844
 1985

New BT's:

- 6" Tamarack bears S28.5°W, 89.7 ft., blazed and scribed: 1/4 S33 BT.
- 5.5" Tamarack bears N32.5°E, 52.7 ft., blazed and scribed: 1/4 S28 BT.


Painted blazes and attached signs as per Standard Specifications for Cadastral Surveys, USFS Region 6, March 1982. Brass disk stamped "LS 1844" nailed to lower end of blazes.

iii
Corner on south slope in open timber. Take Road 51 to Vey Ranch, then take private road opposite ranch drive, north side sheep creek. Go 0.3 miles to clear cut, then north on dirt road to corner.

Compass Declination: 19 1/2°E
Witness: Bernie Sutton

I hereby certify the above described corner monument and/or accessories was established as described on April 14, 1985.

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**



OREGON
JULY 13, 1979
B. A. SUTTON
1848

Office of..... County of.....
 State of....., I hereby certify that the within instrument was filed in this office
 for record on the..... day of....., 19.....
 by
 (COUNTY OFFICIAL) (DEPUTY)

**UNION COUNTY
SURVEYOR**

Date Received 9-18-85
 Date Filed 9-23-85
GPO-798-276
 By G. LANGLITZ DEPUTY
 File No. 80-85 R