


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

In 1882, under GLO Contract 451, Rufus S. Moore set post from which a 7" Pine bears N73°E, 34 lks. and a 6" Pine bears S33°W, 123 lks.

Index File No. V-15



Description of corner evidence found:

NO corner monument or other evidence found.

Description of monument and accessories I established to perpetuate the original location of this corner:

Corner set by single proportioning.  
Set a 2.5"x30" aluminum capped aluminum pipe rising 7" above ground. Set steel fence post 3.0 ft. north of corner.

Cap is stamped:

T5S R35E  
1/4  $\frac{S 27}{S 34}$   
RLS 1844  
1985

New BT's:

8.5" P. Pine bears N4.5°W, 37.6 ft.,  
blazed and scribed: 1/4 S27 BT.  
8" W. Larch bears S49°W, 10.0 ft.,  
blazed and scribed: 1/4 S34 BT.

Painted blazes and attached signs as per Standard Specifications for Cadastral Surveys, USFS Region 6, March 1982. Brass disk stamped "LS 1844" nailed to lower end of blazes.

Corner is on south slope in open timber. Take Road 51 to second Vey Ranch driveway, go west on private road on north side of Sheep Creek 0.5 mile to clear cut. Then go north on road on west side of clear cut 500 ft. north of cut boundary. Corner is 300 ft. west of road.

Compass Declination: 19 1/2°E  
Witness: Bernie Sutton

I hereby certify the above described corner monument and/or accessories was established as described on April 14, 1985.

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR  
*B. Sutton*  
OREGON  
JULY 13, 1979  
B. A. SUTTON  
1848

Office of..... County of.....  
State of..... I hereby certify that the within instrument was filed in this office  
for record on the..... day of....., 19.....

..... by .....  
(COUNTY OFFICIAL) (DEPUTY)

**UNION COUNTY  
SURVEYOR**

Date Received 9-18-85  
☆ GPO-798-276  
Date Filed 9-23-85  
By G. LANGLITZ, DEPUTY  
File No. 82-85 R